



CERTIFICATE OF ACCREDITATION



Midland Asphalt Materials Inc.

in

Tonawanda, New York, USA

has demonstrated proficiency for the testing of construction materials and has conformed to the requirements established in AASHTO R 18 and the AASHTO Accreditation policies established by the AASHTO Committee on Materials and Pavements.

The scope of accreditation can be viewed on the Directory of AASHTO Accredited Laboratories (aashtoresource.org).

A handwritten signature in black ink, appearing to read 'Jim Tymon', written over a horizontal line.

Jim Tymon,
AASHTO Executive Director

A handwritten signature in black ink, appearing to read 'Matt Linneman', written over a horizontal line.

Matt Linneman,
AASHTO COMP Chair

This certificate was generated on 06/23/2026 at 9:34 PM Eastern Time. Please confirm the current accreditation status of this laboratory at aashtoresource.org/aap/accreditation-directory



SCOPE OF AASHTO ACCREDITATION FOR:

Midland Asphalt Materials Inc.

in Tonawanda, New York, USA

Quality Management System

Standard:

R18 Establishing and Implementing a Quality System for Construction Materials Testing Laboratories

Accredited Since:

12/22/2008



SCOPE OF AASHTO ACCREDITATION FOR:

Midland Asphalt Materials Inc.

in Tonawanda, New York, USA

Asphalt Binder

Standard:

Accredited Since:

T49 Penetration of Original Sample of Asphalt Cement

04/15/2011

D5 Penetration of Original Sample of Asphalt Cement

04/15/2011



SCOPE OF AASHTO ACCREDITATION FOR:

Midland Asphalt Materials Inc.

in Tonawanda, New York, USA

Emulsified Asphalt

Standard:

Accredited Since:

T59	Residue by Distillation	12/22/2008
T59	Residue by Evaporation	12/22/2008
T59	Sieve Test	12/22/2008
T382	Viscosity of Emulsified Asphalts Using Rotational Paddle Viscometer at 50°C (122°F)	11/22/2023
T59-T72	Saybolt Furol Viscosity at 50°C (122°F)	12/22/2008
D6933	Sieve Test	12/22/2008
D6934	Residue by Evaporation	12/22/2008
D6997	Residue by Distillation	12/22/2008
D7226	Viscosity of Emulsified Asphalts Using Rotational Paddle Viscometer at 50°C (122°F)	11/22/2023
D7496-D88	Saybolt Furol Viscosity at 50°C (122°F)	12/22/2008